



NATURE

It is a solution of special inorganic aluminium salts with a very good stability during storage.

TECHNICAL DATA (average values)

Form	Aqueous solution
Aspect	Transparent
Colour	Beige
Density at 20°C (g/cm ³)	1.37
pH	approx. 3.5
Chemical composition (%):	
Al as Al ₂ O ₃	12.5 min.
Na as Na ₂ O	< 1
Thermal stability	+5°C to +40°C

PROPERTIES

- Easy handling.
- Environmentally safe.
- The product improved the development of the early-age strength and also the long-age strength of the sprayed concrete.
- Long stability during storage.

FIELDS OF APPLICATION

- WASTE TREATMENT. Waste water clarification, drinking water...
- CONSTRUCTION. Accelerator for easily set in cement and concrete preparation.

STORAGE

AKF-125 AT must be stored between +5°C and +40°C in original closed containers made of plastic, stainless steel. In this case, the stability will be superior to 6 months.

SAFETY CLASSIFICATION FOR STORAGE AND TRANSPORT

It is not classified as dangerous material according to 67/548/EEC Directive on "Classification, packaging and labelling of dangerous substances" and according to EC1272/2008.

DELIVERY

200 l. Plastic drums
1000 l. Plastic containers
Bulk trucks

All of the information contained in this technical sheet is based on our own tests which are considered to be highly reliable. Due to the variety of different conditions of use this information may not be taken as a guarantee nor can we accept any liability with regards to said information.



Producer:
Industrias Químicas del Ebro S.A.
E-50057 Zaragoza (Spain)
Tel. + 34 976 573 625
Fax. +34 976 572 557
e-mail: iqe@iqe.es
Web site: www.iqe.es